

FIBER OPTIC CLOSURES

MINI-CLOSURE 12-48 FIBERS

**This below is our new smallest size (closure dia.188* height 300):
Model:OPT-48S**



Model	Fiber Optic Splice Tray	Capacity (fibers)	Dimension (HxD) mm	Cable Entry and Size
OPT-48S	1-4 pieces of tray with 6 or 12 fibers per tray	24 or 48	300 X 188	1 large oval port with.φ20mm 3 round ports with φ16mm

Accessories

The accessories included in the FOSC: earth wire, nylon tie, buffer tube, emery paper, metal hoop, insulation tape, aluminum foil. earth ground, pressure testing valve, small heat shrinkable fixing sleeve (for small round ports), big heat shrinkable fixing sleeve with branching-off clip (for large oval port).

FIBER OPTIC CLOSURES

CLOSURE 24-96-144 FIBERS

**This below is our (closure dia.210mm* height 420mm):
Model:OPT-96**



Model No.OPT-96A



Model No.OPT-96A+R

Model	Fiber Optic Splice Tray	Capacity (fibers)	Dimensions (HxD) mm	Cable Entry and Size
OPT-96A	1.The optical fibers are taken in from the middle of splicing trays 2. 6 pieces of splice trays (24 fibers per splice tray) Max Capacity:24×6=144 fibers	24 To 144	420 X 210	*Base diameter:16cm *closet ring dia. :21cm *4 small holes +1 oval hole *The diameter of the small holes is 2.0cm.The major axis of the oval hole(inside wall) is 6.cm,and the shorter axis of the oval hole is 4.cm.

Accessories

The accessories included in the FOSC: earth wire, nylon tie, buffer tube, emery paper, metal hoop, insulation tape, aluminum foil. earth ground, pressure testing valve, small heat shrinkable fixing sleeve (for small round ports), big heat shrinkable fixing sleeve with branching-off clip (for large oval port).

FIBER OPTIC CLOSURES

CLOSURE 24-96-144 FIBERS

**This below is our (closure dia.210mm* height 530mm):
Model:CHRB-96**



Model No.OPT-96B



Model No.OPT-96B+R

Model	Fiber Optic Splice Tray	Capacity (fibers)	Dimensions (HxD) mm	Cable Entry and Size
OPT-96B	1.The optical fibers are taken in from the middle of splicing trays 2. 6 pieces of splice trays (24 fibers per splice tray) Max Capacity:24×6=144 fibers	24 To 144	530 X 210	*Base diameter:16cm *closet ring dia. :21 cm *4 small holes +1 oval hole *The diameter of the small holes is 2.0 cm.The major axis of the oval hole(inside wall) is 6.cm,and the shorter axis of the oval hole is 4.cm.

Accessories

The accessories included in the FOSC: earth wire, nylon tie, buffer tube, emery paper, metal hoop, insulation tape, aluminum foil. earth ground, pressure testing valve, small heat shrinkable fixing sleeve (for small round ports), big heat shrinkable fixing sleeve with branching-off clip (for large oval port).