



OPTIC-LINE OPT60M SPLICE PROTECTOR SLEEVE

>>Description

- The Optic-Line Splicer Protector Shrinkable sleeve is applied to the optical fiber closure to fix and protect the optical fiber when splicing.
- The simplex is used for the simplex-fiber. The simplex one realizes the reinforcement by the stainless-steel needles.



>>Main Features

- * Cross-linked polyolefin with one piece clear sleeve design;
- * Pre-installed steel rod or ceramic rod;
- * Different colors of hot fusion insert;
- * Halogen free, RoHS compliant ;
- * Single & ribbon fiber splice protector available;
- * Ideal for providing mechanical reinforcement at the joint point and maintains the optic transmission properties of the fiber optic cable;



>> Specifications

| Reference | Splice Protector | | Fusion Tube | | Steel Rod | | Standard |
|--------------------------|----------------------------|--------|-------------|--------|---------------|-------------|-----------------------|
| | O.D.after recovery (mm) | Length | I.D. (mm) | Length | O.D. (mm) | Length | Package (pcs/pack) |
| | | (mm) | | (mm) | | (mm) | |
| Large sleeve | | | | | | | |
| OPT-61 | 3.0 | 61 | 1.3 | 61 | 1.5 | 55 | 100 |
| OPT-45 | 3.0 | 45 | 1.3 | 45 | 1.5 | 40 | 100 |
| OPT-23 | 3.0 | 23 | 1.3 | 23 | 1.5 | 18 | 100 |
| Standard sleeve | | | | | | | |
| OPT-61M | 2.5 | 61 | 1.3 | 61 | 1.2 | 55 | 100 |
| OPT-45M | 2.5 | 45 | 1.3 | 45 | 1.2 | 40 | 100 |
| OPT-40M | 2.5 | 40 | 1.3 | 40 | 1.2 | 36 | 100 |
| OPT-30M | 2.5 | 30 | 1.3 | 30 | 1.2 | 26 | 100 |
| OPT-25M | 2.5 | 25 | 1.3 | 25 | 1.2 | 21 | 100 |
| Small sleeve | | | | | | | |
| OPT-60A | 2.4 | 60 | 1.3 | 60 | 1.0 | 56 | 100 |
| OPT-60T | 2.0 | 60 | 0.5 | 60 | 1.0 | 56 | 100 |
| OPT-40T | 2.0 | 40 | 0.5 | 40 | 1.0 | 36 | 100 |
| OPT-40TS | 1.7 | 40 | 1.0 | 40 | 0.7 | 39 | 100 |
| OPT-45TS | 1.7 | 45 | 1.0 | 45 | 0.7 | 44 | 100 |
| OPT-50TS | 1.7 | 50 | 1.0 | 50 | 0.7 | 49 | 100 |
| Mini/Micro sleeve | | | | | | | |
| OPT-40S | 1.3 | 40 | 0.5 | 40 | 0.5 | 39 | 100 |
| OPT-25S | 1.3 | 25 | 0.5 | 25 | 0.5 | 24 | 100 |
| OPT-18S | 1.3 | 18 | 0.5 | 18 | 0.5 | 17 | 100 |
| OPT-15S | 1.3 | 15 | 0.5 | 15 | 0.5 | 14 | 100 |
| OPT-10S | 1.3 | 10 | 0.5 | 10 | 0.5 | 9 | 100 |
| Reference | Splice Protector | | Fusion Tube | | Ceramic Rod | | Standard package |
| | (mm) | | I.D.(mm) | | Width (mm) | Height (mm) | (pcs/pack) |
| OPT-6R | 40 | | 2.9 | | 3.8 | 1.65 | 50 |
| OPT-12R | 40 | | 4.1 | | 5.1 | 2.10 | 50 |